

# Basic211


## TECHNICAL FEATURES



### Reference standards :

EN12352: L8H/L8M - P1 - C1 - R0 - A0 - V0 - I0 - F1/F2/F3 - O0/O1/O3 - M3 - T1 - S2  
 EN50293 - EN60529 - EN60598-1 - 2011/65/UE - 2011/305/UE - 2012/19/UE - 2014/30/UE

### OPTICAL CHARACTERISTICS

Light source	1 POWER LED	
Optics	Single-sided	
Color	Amber	
Duration of the optical group	> 50'000 hours	

### ELECTRICAL CHARACTERISTICS

Supply	12/24 Vdc (11 Vdc ÷ 30 Vdc)	
Nominal power	6 W @ 12 Vdc	
Nominal current	500 mA @ 12 Vdc	
Protections	Reverse polarity; Overvoltages	



### FLASHING

Frequency	Defined by External Command (steady light) or 45 flash/min (integrated flashing board) or 60 flash/min (integrated flashing board)	
Duty Cycle	Defined by External Command (steady light) or 50% (integrated flashing board) or 10% (integrated flashing board) or 5% + 5% + 5% (integrated flashing board)	

### MECHANICAL CHARACTERISTICS

Operating temperature	- 25° C / + 55° C	
Lens material	Polycarbonate	
Body material	PA6	
IP protection class	IP65	
Weight	350 g	
Dimensions	Ø 210 mm x 55 mm	
Fixing	4 rear inserts for bracket attachment (not included)	
Wiring	Supplied with 2x0.75 mm² cable	



Rev.2.2 30/06/2021	 Approved TEC	 Approved AQ
-----------------------	--	---