Power supply-Battery kit

TECHNICAL FEATURES

Description
Power supply-Battery kit (connectable to the public lighting grid) including battery and charger for the daytime operation. Option: flashing board (*).

BATTERY FEATURES			
Tipology	Lead AGM		
Nominal voltage	12 Vdc		
Life time	4 years		
Nominal capacity	12 Ah	18 Ah	45 Ah
ELECTRICAL FEATURES			
Input voltage	210 Vac ÷ 250 Vac		
Output voltage	12 Vdc		
*Dimmering	Consuptions reduced to 35% during night-time		
Protections	Over-discharge cutoff; Over-voltages (10kV, 5kA)		
Maximum power consumption	60 W		
*Flashing features	60 flash/min; 10% duty-cycle		
Insulation class	Classe II		
MECHANICAL FEATURES			
IP protection class	IP65	IP65	IP56
Material	Painted metal	Painted metal	Polyester
Dimensions	240 x 280 x 130 mm	280 x 360 x 110 mm	505 x 435 x 215 mm
Total weight	11 Kg	13 Kg	25 Kg
Operative temperature	-25° C ÷ +55° C		
Fixing (pole bracket not included)	60 mm, 90 mm or Band-it	60 mm, 90 mm or Band-it	60 mm or 90 mm

Rev. 3.0		Approved TEC		Approved AQ
28/02/2022				